# DDI602-F2

**Outdoor, Dual Technology detector, 10.587 GHz, selectable 10/20/30 m (33/66/98 ft)**



# DDI602-F2

## Outdoor, Dual Technology detector, 10.587 GHz, selectable 10/20/30 m (33/66/98 ft)

## Technische Spezifikationen

### General

| | |
|---|---|
| Technology | Dual |
| Application type | Vægmontering |
| Anti masking | No |
| Pet immune | No |
| Camera | No |

### Detection

| | |
|---|---|
| Max. detection range | 30 m |
| Microwave frequency (nom.) | 10.587 GHz |
| Undercrawl protection | No |
| Alarm time | 5 sek |

### Wired/wireless

| | |
|---|---|
| Wired-wireless | Kablede |

### Inputs/outputs

| | |
|---|---|
| Relay configuration | Mehrere EOL-Werte |

### Physical

| | |
|---|---|
| Colour | Sølv |
| Material | Høj slag ABS plast med HDPE dæksel, UV stabiliseret |
| Mounting height | 3 bis 6 m |

### Environmental

| | |
|---|---|
| Environment | Udendørs |

### Regulatory

| | |
|---|---|
| Certification | INCERT |

Als innovatives Unternehmen behält sich Kidde Global Solutions das Recht vor, Produktspezifikationen ohne Ankündigungen zu ändern. Für die aktuellsten Produktspezifikationen, besuchen Sie bitte de.firesecurityproducts.com online oder kontaktieren Sie bitte unsere Vertriebsmitarbeiter.