DDI602-F2

Outdoor, Dual Technology detector, 10.587 GHz, selectable 10/20/30 m (33/66/98 ft)



Details

- Electronic range setting: 10/20/30m
- Attractive aesthetics
- 10 to 70° detection angle
- 180° pan & 90° tilt for flexible install
- Sensor module is hidden
- Built in EOL resistors
- High dust & humidity resistance (IP55)
- 5 years warranty

DDI602-F2

Outdoor, Dual Technology detector, 10.587 GHz, selectable 10/20/30 m (33/66/98 ft)

Technische specificaties

General

Technology	Dual
Application type	Vægmontering
Anti masking	No
Pet immune	No
Camera	No

Detection

Max. detection range	30 m
Detection range	30 m
Detection range selection	10, 20 or 30 m
Coverage (field of view)	70°
Microwave frequency (nom.)	10.587 GHz
Undercrawl protection	No
Alarm time	5 sek

Wired/wireless

Wired-wireless	Kablede

Inputs/outputs

Alarm relay characteristic	NC / NO, Volt free relay, signal contact 24 VAC/DC at 50 mA with an integral 25 Ohm series resistor
Anti mask relay characteristic	Volt free relay, signal contact 24 VAC/DC at 50 mA with an integral 25 Ohm series resistor
Relay configuration	Mehrere EOL-Werte

Electrical

Power supply value	9 to 15 VDC
Current consumption	11 mA

Physical

Physical dimensions	147 × 187 × 140 mm
Net weight	323 g
Shipping weight	549 g
Colour	Sølv
Material	Høj slag ABS plast med HDPE dæksel, UV stabiliseret
Mounting height	3 bis 6 m

Environmental

Operating temperature	-30 to +65°C
Environment	Udendørs

Regulatory

Certification	INCERT

Als een bedrijf van innovatie behoudt Kidde Global Solutions zich het recht voor productspecificaties zonder kennisgeving te wijzigen. Ga voor de nieuwste productspecificaties online naar be.firesecurityproducts.com of neem contact op met uw verkoopvertegenwoordiger.

Last updated on 12 November 2026 - 18:57