# VV622-PLUS

**Seismic detector for ATMs and night safe deposit boxes, Form C relay**



# VV622-PLUS

## Seismic detector for ATMs and night safe deposit boxes, Form C relay

## Specyfikacja techniczna

### General

| | |
|---|---|
| Application type | Pengeautomat (ATM), Natlige bankbokse |
| Tamper protection | Temperature 84°C, drill shield, opening contact, pry-off contact |
| Alarm indication | LED-indication screw no. 3 |
| Low voltage alarm | 7.5 V |

### Detection

| | |
|---|---|
| Range | 3 to 14 m radius |
| Sensitivity adjustment | 5 steps of approx. 6 dB each |

### Inputs/outputs

| | |
|---|---|
| Alarm contact | Form A solid state relay, max series resistance 35 ohm |
| Test output | Yes |

### Physical

| | |
|---|---|
| Colour | Grå (RAL 7035) |

### Regulatory

| | |
|---|---|
| Certification | VdS |

Będąc firmą innowacyjną, Kidde Global Solutions zastrzega sobie prawo do zmian w specyfikacji wyrobów bez uprzedzenia. W celu uzyskania najnowszych specyfikacji prosimy o wizytę na stronach pl/firesecurityproducts.com lub kontakt z przedstawicielem handlowym.

Last updated on 12 November 2026 - 18:57