
TCC-0007

IS Echolot/Blinkleuchte, 24 V, gelbe Linse

IS Sonos sounder beacon

The IS Sonos sounder beacon has been approved for use in potentially explosive atmospheres for Group I (Mining) & Group II (Above Ground) applications and incorporates a high Ingress Protected IP66 enclosure.
The sounder beacon unit incorporates a two stage alarm option and has a total of 32 selectable tones, selectable via a dip switch on the PCB and produces up to 105 dB at 1 meter. A specially designed time saver base enables quick and easy installation of this unit with no extra cabling to be made to the head of the unit.
Connections are made to the base during the initial wiring phase which results in a faster more reliable installation. The sounder head simply twists & clicks into the pre-fixed base on commissioning avoiding any additional wiring & connections.
Further details can be found on the installation sheet' This unit must be used in conjunction with an approved Zener Barrier or Galvanic Isolator. The characteristics should not exceed Uo: 28 V, Io: 93 mA, Po: 660 mW, Ci: 0, Li 0. The minimum value of Uo should not drop below 23.6 V and the minimum value of Io should not drop below 50 mA.



Einzelheiten

- Zugelassen durch ATEX, IECEx Gruppe I MI Ex ia I Ma Gruppe II IGD Ex ia IIC T6 Ga, Ex ia IIIC T85˚C Da Zonen 0, 1, 2, 20, 21 & 22 Konform mit: EN 60079-0:2012 + All:2013 (IEC 60079-0:2011) EN-60079-11:2012 + (IEC 60079-11:2011)
- Diodenpolarisiert und mit Endwiderständen kompatibel
- Weiße Basisversion verfügbar MOQ gelten
- Staubdicht und witterungsbeständig
- Anwendungen: Feuer, Sicherheit, Prozesskontrolle und allgemeine Signalisierung

TCC-0007

IS Echolot/Blinkleuchte, 24 V, gelbe Linse

Technische Spezifikationen

Electrical

Power supply type	24 VDC

VAD

Colour	Bernstein

Physical

Net weight	0.33 kg
Colour	Red
Mounting type	Base mount
Mounting position	Ceiling, Wall
Mounting base	Deep
Material	Flame retardant Polycarbonate

Environmental

Vandal proof	No
Operating temperature	-40 bis +55ºC
Relative humidity	>90% bei 20ºC
IP rating	IP66

Regulatory

Compliancy	CE, REACH, RoHS 3, WEEE
Certification	CENELEC/ATEX, CPR
Standards	ATEX (EMT17ATEX0012X) IECEx (EMT 17.0005X)

KIDDE GLOBAL SOLUTIONS

Als innovatives Unternehmen behält sich Kidde Global Solutions das Recht vor, Produktspezifikationen ohne Ankündigungen zu ändern. Für die aktuellsten Produktspezifikationen, besuchen Sie bitte de.firesecurityproducts.com online oder kontaktieren Sie bitte unsere Vertriebsmitarbeiter.