ATS1476

(10 pack) Hitag II card with magstripe

Product Overview

The cards are PVC made and have a HICO-Magstripe. Both the smart ship and antenna are embedded inside the card. Printing is possible on the card using any industry standard printer. The cards feature a programmable magnetic strip for Time & Attendance or other applications. The cards are used on the ATS proximity readers as well as the magstripe readers. Printing is possible on the card using any industry standard printer and because each card has superior finished surface you will always have excellent printing results.



Details

- Read/Write capability
- Ability to program a unique 4-billion, 4-byte security code
- 4 memory areas for credit applications
- Packed by 10

ATS1476

(10 pack) Hitag II card with magstripe

Technical specifications

System

Reading distance	0 to 30 cm
Custom data model	No
Supported readers	ATS Proximity Readers, Magstripe Readers

Technology

Credential type	Magstripe, Proximity
Credential operating frequency	125 KHz
Supported technology 125 kHz	HiTag 2

Printing

Direct surface printing	Yes

Ordering information

Minimum order quantity	1
Cards/tags in package	10

Physical

Material	PVC
Form factor	CR80 (Credit)
Physical dimensions	86 x 54 mm

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 18 June 2026 - 14:24