VE1120

Vector PIR, DSP, 20m, 11 curtains



Details

- Passive Infra Red motion sensor
- 3-Step Gliding Focus Curtain mirror
- Plug-in electronics
- Sealed optics
- "V2E" signal processing for false alarm immunity
- Cloak and umbrella immunity
- Full under crawl detection
- Selectable coverage pattern using mirror masks
- Auto focus with constant range sensitivity
- No adjustment required for different mounting heights
- Tolerates wall angle deviation
- EN50131-2-2 Grade 2 certified
- Several European approvals

VE1120
Vector PIR, DSP, 20m, 11 curtains

Technische specificaties

General

Technologie	PIR
Type toepassing	Wall mount
Anti-maskering	No
Ongevoelig voor huisdieren	No
Camera	No
Signaalverwerking	Vector Verified Enhanced (VE2)
Afneembeveiligingskit	ST400 (optional)

Detection

Max. detectiebereik	20 m
Detectiebereik	20 m
Onderkruipbeveiliging	Yes
Alarmgeheugen	Yes
Alarmtijd	3 s

Wired/wireless

Bedraad / draadloos	Wired

Inputs/outputs

Relais configuratie	Isolated or 4k7 EOL
Stuurdraden op afstand	Day/Night, Walk test

Physical

Kleur	White
Montagehoogte	1.8 to 3 m

Environmental

Omgeving	Indoor

Regulatory

EN50131 Grade	Grade 2

Als een bedrijf van innovatie behoudt Kidde Global Solutions zich het recht voor productspecificaties zonder kennisgeving te wijzigen. Ga voor de nieuwste productspecificaties online naar be.firesecurityproducts.com of neem contact op met uw verkoopvertegenwoordiger.

Last updated on 12 November 2026 - 18:57