# TVD-6105

## TruVision HD-TVI Analog Dome Camera, 8MPX, 2,7 ~ 13,5MM Motoriseret linse, Ægte D/N, WDR, 60m IR HD-TVICoax udgang, Coax OSD kontrol, 12VDC / 24AC, IP67

### Overview

The TruVision line includes a comprehensive family of HD-TVI infrared (IR) cameras for stand-alone or integrated installations.  Designed for optimal image quality over existing coaxial cable, options are available at up to 8Mpx resolution.

Ideal for improving video quality of existing analog surveillance system installations ranging from convenience stores to retail mall parking lots, the TruVision HD-TVI line has the right cameras for your new or existing project and can help you stay within budget constraints without compromising security needs.

The cameras have true day/night capabilities, providing color images by day and black-and-white images under IR operation in low light applications. TruVision HD-TVI cameras are available with either fixed lens or varifocal lens.

Form factors include dome, traditional bullet and turret cameras . Bullet models offer a familiar form factor that features a pre-installed wall mount with cable management. All models are IP67 rated for outdoor installation and select dome models are available with an IK10 vandal-rated enclosure.

All TruVision HD-TVI cameras are designed to install quickly and easily, right out of the box, so you can be up and running in no time.



### Detaljer

- 8MPx HD-TVI resolution
- HD-TVI technology for transmitting high quality video over existing coax cable
- True day/night functionality and infrared illuminators with Smart IR function for capturing images in various lighting scenarios
- IR range of up to 80 m
- IP67 environmental rating
- True wide dynamic range
- 2.7 to 13.5 mm lens
- 12 VDC or 24VAC
- Provide OSD functionality via TruVision up the coax control
- Back box included

# TVD-6105

## TruVision HD-TVI Analog Dome Camera, 8MPX, 2,7 ~ 13,5MM Motoriseret linse, Ægte D/N, WDR, 60m IR HD-TVICoax udgang, Coax OSD kontrol, 12VDC / 24AC, IP67

## Tekniske specifikationer

### General

| | |
|---|---|
| Technology | HD-TVI-analog |
| Video standard | NTSC, PAL |
| Image settings | Espejo |
| Video output | BNC Compuesto PAL / NTSC, HD-TVI |

### Camera

| | |
|---|---|
| Max. resolution | 8 MPX (4K) |
| Sensor scan | Progresivo |
| Sensor type | CMOS |
| Effective pixels (H x V) | 3840 x 2160 |
| Shutter time | 1/12.5s (PAL) or 1/15s (NTSC) to 1/50,000 |

### Lighting performance

| | |
|---|---|
| WDR type | WDR Verdadero |
| WDR | 130 dB |
| Day/night | Verdadero Día/Noche |
| Motorized IR cut filter | Yes |
| Color sensitivity | 0.003 Lux @ (F1.2, AGC ON) |
| B/W sensitivity | 0 Lux with IR |
| Infrared (IR) | Yes |
| IR range | 60m |

### Lens

| | |
|---|---|
| Lens type | Varifocal motorizada |
| Focal length | 2.7 to 13.5 mm |
| f-stop | f1.2 |
| Auto iris | Yes |
| Auto focus | Yes |
| Motorized zoom | Yes |

### Electrical

| | |
|---|---|
| Operating voltage | 12VDC or 24VAC |
| Power supply type | 12 VCC, 24 VAC |
| Power consumption | 8.2 W Max. |

### Physical

| | |
|---|---|
| Physical dimensions | 84.5 x 92 x 255.1 mm |
| Net weight | 925 g |
| Colour | Gris (Pantone 428c) |
| Material | Aluminium |
| Form Factor | Dome |

### Environmental

| | |
|---|---|
| Impact rating | IK10 |
| Environment | Indendør, Udendørs |
| Operating temperature | -40 to 60°C |
| Relative humidity | 90% or less (non-condensing) |
| IP rating | IP67 |

### Regulatory

| | |
|---|---|
| Compliancy | CE, REACH, RoHS, WEEE |

### Kompatible produkter

| Kategori | Reference | Beskrivelse |
|---|---|---|
| Brackets & Mounts | TVD-CB3 | Monteringsskål til TruVison og UltraView domekameraer. |
| Brackets & Mounts | TVD-LWB-2 | Truvision Dome L-formet vægbeslag til indendørs og udendørsbrug. |

Kidde Global Solutions er et innovativt selskab og forbeholder sig ret til at ændre produktspecifikationer uden varsel. De nyeste produktspecifikationer kan du finde på dk.firesecurityproducts.com eller ved at kontakte din salgsrepræsentant hos.

Last updated on 12 November 2026 - 18:57