ATS1180M

Czytnik kart MIFARE DESFire EV1/EV2/EV3 dla rozwiązań mobilnych

Product overview

The ATS MIFARE DESFire EV1/EV2/EV3 readers connect directly to the control panel using the ATS databus. Communication to Axon and Advisor Advanced control panels is AES encrypted. In secure mode, card to reader data is also AES encrypted providing secure communication from the card to the processing unit. The readers are configured locally through keypad and control panel menu and the address is configures using the ATS1482 addressing card. Select secure cards from the ATS145x secure card series. The reader is also prepared to support future mobile credentials.
The reader offers a Request To Exit input and one open collector output that can be used to control a door relay or door strike.

The ATS118xM Mifare Desfire readers are designed to transfer card data in a secure and reliable way in various environments. The card data is by default secured by an Aritech own security key, but can be changed easily in Axon or Advisor Advanced control panels to any custom required key.
The readers can optionally be set to read MIFARE CSN numbers instead in unsecure mode.

Communication

The reader communicates in a secure way over the ATS LAN databus to Axon or Advisor control panels using AES encryption, securing the data from the card until being processed.

Design

The unique design of the housing guarantees that the reader can be used in the most demanding surroundings having IP67 and IK-09 rating. The reader can be installed directly on to a metal surface without any insulation.
Mounting brackets and weather protection covers provide extend the available applications.



Szczegóły

- Bezpieczny czytnik ATS MIFARE DESFire EV1/EV2/EV3
- Gotowy do obsługi mobilnych identyfikatorów przez Bluetooth
- Wspiera MIFARE w Trybie Chronionym (Secure Mode) lub odczyt CSN/UID 4- lub 7-bajtowy w Trybie Niechronionym (Unsecure Mode)
- Obsługuje karty serii ATS145x lub karty klienta
- Bezpieczna komunikacja z centralą Axon / Advisor Advanced / CDC4 dzięki szyfrowaniu AES-128 bit
- Wytrzymała, formowana obudowa z tworzywa o smukłym kształcie
- Montaż wewnętrzny lub zewnętrzny
- Interfejs magistrali ATS
- Wejście „Żądanie wyjścia” (RTE)
- Wyjście typu Otwarty Kolektor (Open Collector, otwarcie drzwi)
- Obsługiwane od Advisor Advanced MR4.9 oraz Axon MR1.0
- Przygotowany do konfiguracji przez NFC

ATS1180M

Czytnik kart MIFARE DESFire EV1/EV2/EV3 dla rozwiązań mobilnych

Specyfikacja techniczna

System

Reading distance	Tryb chroniony: maks. 2 cm Tryb niechroniony: maks. 5 cm Bluetooth – zależnie od urządzenia i ustawień
Max. reader distance to panel	1500 m
CSN (Card Serial Number)	Yes
Custom data model	Yes
Supported card types	MIFARE® Classic UID, MIFARE® DESFire UID, MIFARE® DESFire® EV1, MIFARE® DESFire® EV2, MIFARE® DESFire® EV3
Addressing type	Kartenadressierung
No. of LEDs	3

Technology

Reader type	Smartcard
Reader operating-transmitting frequency	13.56 MHz
Supported technology 13.56 MHz	MIFARE Classic (CSN), MIFARE DESFire (CSN), MIFARE DESFire EV1 (Aritech), MIFARE DESFire EV1 (CSN), MIFARE DESFire EV1 (benutzerdefinierte Daten), MIFARE DESFire EV2 (Aritech), Mifare DESFire EV2 (CSN), Mifare DESFire EV2 (Benutzerdefinierte Daten), MIFARE DESFire EV3 (CSN), MIFARE DESFire EV3 (custom data)
Mifare type	ISO14443A
No. of Mifare bytes CSN	4 Byte (nicht eindeutig), 4 Byte (S50), 7 Byte (S50), 7 Byte (S70)

Interface & connections

Interface	ATS RS-485
Connector type	Zopf
Pigtail length	2 m

Inputs/outputs

Inputs	Aufforderung zum Beenden
Outputs	1 Open Collector (10 mA)

Tamper type

Pry-off tamper	Yes

Operation

Stand-alone	No
PIN keypad	No

Electrical

Operating voltage	10.8 do 30 VDC
Current consumption	55 mA przy 13,8 VDC (norma) 85 mA przy 13,8 VDC (maks.)

Physical

Physical dimensions	140 x 44 x 20 mm
Net weight	240 g
Shipping weight	275 g
Colour	Schwarz
Material	Plastik
Form factor	Slimline
Mounting Type	Oberflächenmontage

Environmental

Operating temperature	-40 do +55°C
Storage temperature	-40 do +55°C
Relative humidity	<95%, bez kondensacji
Environment	Drinnen, Draussen
IP rating	IP67 IK09

Regulatory

Compliancy	CE

Będąc firmą innowacyjną, Kidde Global Solutions zastrzega sobie prawo do zmian w specyfikacji wyrobów bez uprzedzenia. W celu uzyskania najnowszych specyfikacji prosimy o wizytę na stronach pl/firesecurityproducts.com lub kontakt z przedstawicielem handlowym.

Last updated on 12 November 2026 - 18:57