# ATS1180M

## Leitor de cartões MIFARE DESFire EV1/EV2/EV3 (Seguro) com saída e entrada RTE em design fino, preparado para soluções móveis.

### Product overview

The ATS MIFARE DESFire EV1/EV2/EV3 readers connect directly to the control panel using the ATS databus. Communication to Advisor Advanced control panels is AES encrypted. In secure mode, card to reader data is also AES encrypted providing secure communication from the card to the processing unit. The readers are configured locally through keypad and control panel menu and the address is configures using the ATS1482 addressing card. Select secure cards from the ATS145x secure card series. The reader is also prepared to support future mobile credentials.
The reader offers a Request To Exit input and one open collector output that can be used to control a door relay or door strike.

The ATS118xM Mifare Desfire readers are designed to transfer card data in a secure and reliable way in various environments. The card data is by default secured by an Aritech own security key, but can be changed easily in Advisor Advanced control panels to any custom required key.
The readers can optionally be set to read MIFARE CSN numbers instead in unsecure mode.

### Communication

The reader communicates in a secure way over the Advisor databus to Advisor control panels using AES encryption, securing the data from the card until being processed.

### Design

The unique design of the housing guarantees that the reader can be used in the most demanding surroundings having IP67 and IK-09 rating. The reader can be installed directly on to a metal surface without any insulation.
Mounting brackets and weather protection covers provide extend the available applications.



### Detalhes

- Leitor seguro ATS MIFARE DESFire EV1/EV2/EV3
- Preparado para credenciação móvel utilizando Bluetooth
- Suporta Mifare seguro (modo seguro) ou Mifare CSN/UID de 4 ou 7 bytes (modo não seguro)
- Utilizar cartões seguros da série ATS145x ou cartões de cliente
- Comunicação segura utilizando encriptação AES-128 bit entre o leitor e o painel de controlo Advisor Advanced / CDC4
- Caixa robusta em plástico moldado com design fino
- Instalação no interior ou no exterior
- Interface de Databus ATS
- Entrada de RTE
- Saída de coletor aberto (porta aberta)
- Suportado a partir do Advisor Advanced MR4.9
- NFC preparado para fins de configuração

# ATS1180M

## Leitor de cartões MIFARE DESFire EV1/EV2/EV3 (Seguro) com saída e entrada RTE em design fino, preparado para soluções móveis.

## Especificações técnicas

### System

| | |
|---|---|
| Reading distance | Seguro: máx. 2 cm<br>Não seguro: máx. 5 cm<br>Bluetooth dependendo do dispositivo móvel e das definições |
| Max. reader distance to panel | 1500 m |
| CSN (Card Serial Number) | Yes |
| Custom data model | Yes |
| Supported card types | MIFARE® Classic UID, MIFARE® DESFire UID, MIFARE® DESFire® EV1, MIFARE® DESFire® EV2, MIFARE® DESFire® EV3 |
| Addressing type | Kartenadressierung |
| No. of LEDs | 3 |
| Language installation manual | Portuguese, Portugal |

### Technology

| | |
|---|---|
| Reader type | Smartcard |
| Reader operating-transmitting frequency | 13.56 MHz |
| Supported technology 13.56 MHz | MIFARE Classic (CSN), MIFARE DESFire (CSN), MIFARE DESFire EV1 (Aritech), MIFARE DESFire EV1 (CSN), MIFARE DESFire EV1 (benutzerdefinierte Daten), MIFARE DESFire EV2 (Aritech), Mifare DESFire EV2 (CSN), Mifare DESFire EV2 (Benutzerdefinierte Daten), MIFARE DESFire EV3 (CSN), MIFARE DESFire EV3 (custom data) |
| Mifare type | ISO14443A |
| No. of Mifare bytes CSN | 4 Byte (nicht eindeutig), 4 Byte (S50), 7 Byte (S50), 7 Byte (S70) |

### Interface & connections

| | |
|---|---|
| Interface | ATS RS-485 |
| Connector type | Zopf |
| Pigtail length | 2 m |

### Inputs/outputs

| | |
|---|---|
| Inputs | Aufforderung zum Beenden |
| Outputs | 1 Open Collector (10 mA) |

### Tamper type

| | |
|---|---|
| Pry-off tamper | Yes |

### Operation

| | |
|---|---|
| Stand-alone | No |
| PIN keypad | No |

### Electrical

| | |
|---|---|
| Operating voltage | 10.8 a 30 VDC |
| Current consumption | 55 mA @13.8 VDC normal<br>85 mA @13.8 VDC max. |

### Physical

| | |
|---|---|
| Physical dimensions | 140 x 44 x 20 mm |
| Net weight | 240 g |
| Shipping weight | 275 g |
| Colour | Schwarz |
| Material | Plastik |
| Form factor | Slimline |
| Mounting Type | Oberflächenmontage |

### Environmental

| | |
|---|---|
| Operating temperature | -40 a +55°C |
| Storage temperature | -40 a +55°C |
| Relative humidity | <95%, noncondensing |
| Environment | Drinnen, Draussen |
| IP rating | IP67<br>IK09 |

### Regulatory

| | |
|---|---|
| Compliancy | CE |

Como empresa de inovação, a Kidde Global Solutions reserva o direito de alterar as especificações do produto sem aviso prévio. Para obter informações sobre as especificações mais recentes do produto, visite pt.firesecurityproducts.com online ou contate o departamento comercial.

Last updated on 12 November 2026 - 18:57