AS506

Outdoor siren with single red beacon



Details

- Attractive high quality shaped housing
- Double piezo sounder with 114 dB @ 1m sound output
- Vertical or horizontal mounting
- Fully potted electronics
- Strobe flash light
- Selectable comfort LED indication
- Pry-off and opening tamper detection
- Self detection of cable cutting or tampering
- Installer friendly
- Hold-off polarity selection
- Independently hold-off for both beacon and siren
- A choice of cut off time
- Selectable tamper configuration

AS506

Outdoor siren with single red beacon

Technical specifications

General

Accessory group	Sirene
Type	Udendørs sirene
Sounder output (dB @ distance)	114 dB at 1 m (typical)
Comfort LED	Yes
Cut-off timer	3, 5, 10, 20 min
Frequency	0.5 to 3 kHz
On-board self-activating battery	10.8 V / 280 mAh

Flash specifications

Flash frequency	50 to 60 flashes/min

Electrical

Operating voltage	10 to 14.5 VDC
Current consumption	350 mA 40 mA (standby, with NiCd battery) 20 mA (standby, without battery)

Physical

Physical dimensions	210 x 300 x 55 mm (W x H x D)
Net weight	1011 g
Material	Polycarbonat
Material	Polycarbonate (3 mm)

Environmental

Operating temperature	-25 to +55°C
IP rating	IP54

Security

PCB protection	Fully potted
Tamper & pry-off	Yes
Low voltage detection	Yes

Sounder

	Double piezo

Accessories

Metal inner cover	Optional

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 27 May 2026 - 17:12