KL710

KILSEN KC700 Series conventional heat detector

General

With outstanding performance, efficiency and durability, the KL700 series conventional fire detectors is the ideal solution for every installation. They are designed specifically for use with Kilsen conventional fire panels, but may also be connected to most 3rd party industry standard conventional fire panels.

A fire detector for every need

With an attractive design and advanced features, the KL700 series has been designed to cope with difficult and even extreme situations. The range includes optical and heat detectors with a universal base that suits every application, including a variant that even compensates for uneven installation surfaces. All detectors support an integral locking mechanism for extra security as well as the connection of a remote indicator.

KL710 Heat Detector

This detector raises an alarm when the temperature exceeds a fixed temperature level or when the programmed rate of the increase of temperature is exceeded. They are used where a fire could cause an abrupt elevation of the temperature, or where smoke of controlled combustion, aerosols, etc. do not allow the use of any other type of detector.

KL731 Photoelectric Smoke Detectors

These detectors use the Tyndall effect of smoke in the chamber to detect a fire. It can detect a smouldering fire (without flames). They are normally used in areas where possible fires generate visible smoke, like plastics, polystyrene, PVC, etc.

The KL731 is available in either white or black colour variants.



Details

- Full line consisting of Optical and Heat detectors
- An ultra-fine grid prevents the ingress of dust and insects in smoke detectors
- Attractive, low-profile design
- EN54 and CPD certified
- Innovative base compensates for uneven surfaces
- Field exchangeable optical chamber for ease of maintenance in optical detectors

KL710

KILSEN KC700 Series conventional heat detector

Technical specifications

Electrical

Operating voltage	18 to 28 VDC
Current consumption	Quiescent at 24 VDC 70 µA Alarm at 24 VDC <100 mA

Output

Remote alarm output	<100 mA

Physical

Physical dimensions	45 x 99 mm
Colour	Branco (RAL 9010-P)
Mounting type	Montagem na base

Environmental

Operating temperature	-10 to +70°C
Storage temperature	-10 to +80°C
Relative humidity	0 to 95% noncondensing
Environment	Indendør
IP rating	IP42

Regulatory

Certification	EN54-5
Approvals*	EN54 (BOSEC)

Radio-active source

NA

Average activity

NA

Heat specification

Class A2R (60°C and 8°C/min)

Number of detectors per zone

20

Compatible products

Category	Reference	Description
Detection device	KZ700	KILSEN KC700 series standard point detector base
Detection device	KZD705	Kilsen KC700 / KA700 / KM300 series deep point detector base
Notification device	PA25/3L	Conventional remote indicator

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 14 March 2025 - 12:57