ATS1197

ATS Smart Card Reader with keypad supplied with 2 m cable



Details

- Full epoxy filled weather proof construction
- Keypad

ATS1197

ATS Smart Card Reader with keypad supplied with 2 m cable

Technische specificaties

System

Max. reader distance to panel	1500
Supported card types	HiTag2
Addressing type	Direccionamiento de la Tarjeta, Direccionamiento del Teclado, Direccionamiento del Software
No. of LEDs	3 LEDs

Technology

Reader type	Nærhed, Tarjeta Inteligente
Reader operating-transmitting frequency	125 KHz
Supported technology 125 kHz	HiTag 2

Interface & connections

Interface	ATS RS-485
Connector type	Svinesvans
Pigtail length	200

Inputs/outputs

Inputs	Solicitud de salida
Outputs	1 Colector abierto (50 mA)

Tamper type

Pry-off tamper	Yes

Operation

PIN keypad	Yes

Electrical

Power supply value	8.5 to 14 VDC
Current consumption	110 40

Physical

Physical dimensions	140 × 121 × 22 mm
Colour	Gris oscuro
Mounting Type	Montaje en Superficie

Environmental

Operating temperature	-40 to +50°C
Environment	Udendørs
IP rating	IP66

Als een bedrijf van innovatie behoudt Kidde Global Solutions zich het recht voor productspecificaties zonder kennisgeving te wijzigen. Ga voor de nieuwste productspecificaties online naar be.firesecurityproducts.com of neem contact op met uw verkoopvertegenwoordiger.

Last updated on 12 November 2026 - 18:57