TVT-6101

TruVision HD-TVI Analog Turret Camera, 5 MP, 2.8 mm lens, WDR, 30 m IR, HD-TVI output, IP67

Product overview

The TruVision line includes a comprehensive family of HD-TVI infrared (IR) cameras for stand-alone or integrated installations. Designed for optimal image quality over existing coaxial cable, options are available at up to 8 MP resolution.

Ideal for improving video quality of existing analog surveillance system installations ranging from convenience stores to retail mall parking lots, the TruVision HD-TVI line has the right cameras for your new or existing project and can help you stay within budget constraints without compromising security needs.

The cameras have true day/night capabilities, providing color images by day and black-and-white images under IR operation in low light applications. TruVision HD-TVI cameras are available with either fixed lens or varifocal lens.

Form factors include dome, traditional bullet and turret cameras . Bullet models offer a familiar form factor that features a pre-installed wall mount with cable management. All models are IP67 rated for outdoor installation and select dome models are available with an IK10 vandal-rated enclosure.

All TruVision HD-TVI cameras are designed to install quickly and easily, right out of the box, so you can be up and running in no time.



Details

- 5MPx HD-TVI resolution
- HD-TVI technology for transmitting high quality video over existing coax cable
- True day/night functionality and infrared illuminators with Smart IR function for capturing images in various lighting scenarios
- IR range of up to 30 m
- IP67 environmental rating
- True wide dynamic range
- 2.8 mm lens
- 12 VDC
- Adapter plate included
- Provide OSD functionality via TruVision up the coax control

TVT-6101

TruVision HD-TVI Analog Turret Camera, 5 MP, 2.8 mm lens, WDR, 30 m IR, HD-TVI output, IP67

Technical specifications

General

Technology	HD-TVI-analog
Video standard	NTSC, PAL
Image settings	Mirror
Video output	BNC Composite PAL / NTSC, HD-TVI

Camera

Max. resolution	5 MP
Sensor scan	Progressive
Sensor type	CMOS
Effective pixels (H x V)	2560 x 1944
Shutter time	1/25 s (PAL) or 1/30 s (NTSC) to 1/50,000

Lighting performance

WDR type	True WDR
WDR	130 dB
Day/night	True Day/Night
Motorized IR cut filter	Yes
Color sensitivity	0.003 Lux @ (F1.2, AGC ON)
B/W sensitivity	0 Lux with IR
Infrared (IR)	Yes
IR range	30 m

Lens

Lens type	Fast
Focal length	2.8 mm
f-stop	f1.2
Auto iris	Yes

Electrical

Operating voltage	12 VDC
Power supply type	12 VDC
Power consumption	5.8 W Max.

Physical

Physical dimensions	Ø 110 x 91 mm
Net weight	310 g
Colour	Grigio (Pantone 428c)
Material	Aluminium
Form Factor	Turret

Environmental

Environment	Indendør, Udendørs
Operating temperature	-40 to +60°C
Relative humidity	<90% noncondensing
IP rating	IP67

Regulatory

Compliancy	CE, REACH, RoHS, WEEE

Compatible TruVision Recorders/Encoders

TVR12HD	(View max. 1080p, Record max. 1080p @ 12 fps)
TVR44HD	(Record/View max. 1080p)
TVR15HD	(Record/View max. 5Mpx @ 12fps)
TVR45HD	(Record/View max. 5Mpx @ 12fps)
TVR46HD	
TVE-110/410/810/1610	
TVE-120/420/820/1620	

Compatible products

Category	Reference	Description
Brackets & Mounts	TVD-BB3	TruVision dome back box used with TVW-56xx Wedge, TVD-6/7 Series Domes
Brackets & Mounts	TVD-BB3A	TruVision dome angled back box TVW-56xx Wedge, TVD-6/7 Series Domes
Brackets & Mounts	TVD-CB3	TruVision Dome 3 inch Cup Base for TruVision varifocal turret cameras
Brackets & Mounts	TVD-M2-WM	TruVision indoor dome wall mount

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 18 June 2026 - 14:28