# DDI602AM-F2

**Outdoor Dual Technology/AM detector 10.587 GHz 10/20/30m selectable**



# DDI602AM-F2

## Outdoor Dual Technology/AM detector 10.587 GHz 10/20/30m selectable

## Technische Spezifikationen

### General

| | |
|---|---|
| Technology | Dualna |
| Application type | Uchwyt ścienny |
| Anti masking | Yes |
| Pet immune | No |
| Camera | No |

### Detection

| | |
|---|---|
| Max. detection range | 30 m |
| Microwave frequency (nom.) | 10.587 GHz |
| Undercrawl protection | No |
| Alarm time | 5 sek |

### Wired/wireless

| | |
|---|---|
| Wired-wireless | Verdrahtet |

### Inputs/outputs

| | |
|---|---|
| Relay configuration | Wiele wartości EOL |

### Physical

| | |
|---|---|
| Colour | Silber |
| Material | Hochschlagfester ABS Kunststoff mit HDPE Abdeckung, UV stabilisiert |
| Mounting height | 3 do 6 m |

### Environmental

| | |
|---|---|
| Environment | Draussen |

### Regulatory

| | |
|---|---|
| EN50131 grade | Grad 3 |

Als innovatives Unternehmen behält sich Kidde Global Solutions das Recht vor, Produktspezifikationen ohne Ankündigungen zu ändern. Für die aktuellsten Produktspezifikationen, besuchen Sie bitte de.firesecurityproducts.com online oder kontaktieren Sie bitte unsere Vertriebsmitarbeiter.