# FE260-325

## Door holder, universal adjustable tube, 400 N, with release button, 325 mm

### General

The FE260-325 is a floor/wall mount door holder with a universal adjustable tube with a reach of 325 mm when used in 180° configuration and 300 mm used in 90° configuration. Which offers a 400 N holding force and a release button.

### Magnet construction

The magnet is constructed with a pressed coil and anti-remenance pin, giving it a protection of IP54. The protection diodes are integrated into this construction.

### Adjustable

The “head” of the FE260-325 allow for two mounting options. The first being the 180° configuration, which is normally used when the door holder is mounted on the wall. In this configuration, the magnet is located “on-top” of the tube.

And the second configuration being the 90° configuration, which is normally used when the door holder is mounted on the ground. In this configuration, the magnet is located on the “side” of the tube, as shown in the picture.

To allow for even more flexibility, the tube can also be cut shorter to match the exact distance required.

### Installer friendly

- For practical ease of installation, the door holder comes complete with electrical screw terminals.
- The base is predrilled in a practical, standard format for rapid mounting.
- The door holder is supplied complete with a keeper plate, which offer angular adjustment.

### Approvals

The FE260-325 is fully approved according to EN1155.



### Details

- Low power - 1.6 W
- 400 N holding force
- Anti-remnant ejector
- Spark suppression diode and reverse polarity protection
- Release button
- EN1155 approved
- Adjustable
- Keeper plate included

# FE260-325

## Door holder, universal adjustable tube, 400 N, with release button, 325 mm

## Technical specifications

### General

| | |
|---|---|
| Holding force N (Newton) | 400 |
| Release button | Yes |
| Spark supression diode | Yes |
| Reverse polarity protection | Yes |

### Electrical

| | |
|---|---|
| Power supply type | 24 VDC |
| Power consumption | 1.6 W |
| Duty cycle | 100% |

### Physical

| | |
|---|---|
| Physical dimensions | 80 x 90 x 300 mm (W x H x D) 90° setup<br>80 x 90 x 325 mm (W x H x D) 180° setup |

### Environmental

| | |
|---|---|
| IP rating | IP54 (magnet)<br>IP42 (connection) |

### Regulatory

| | |
|---|---|
| Standards | EN1155 |

### Compatible products

| Category | Reference | Description |
|---|---|---|
| Door Holders | FE527 | Standard Anchorplate for FE500 Series Doormagnets |
| Door Holders | FE529 | Swivel Anchorplate for FE500 Series Doormagnets |

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 16 October 2026 - 11:43